

Technical Datasheet

tasker® TSK1125 - 1x2,50 mm²

Shielded Speaker Cable



CATEGORY Shielded Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional loudspeakers and premade cables

- A:** Black Soft **PVC** sheath.
Outer Cable Diameter Ø 6,10 (±0,10) mm.
- B:** Shielding in O.F.C. red copper spiral covering 100% with a formation of 128x0,15 mm. Nom. section of the shield 1x2,50 mm².
- C:** Core Insulation with grey PVC.
Dimension Ø 3,40 (±0,10) mm.
- D:** O.F.C. red copper formation 128x0,15 mm.
Nom. Cross section 1x2,50 mm².

MARKING tasker® TSK1125 – 1x2,50 mm² - O.F.C. COAXIAL SHIELDED SPEAKER CABLE+
- Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			