


Technical Datasheet

tasker® C251 – 20x0,14 mm² - LiYCY Cable



NOTE
CATEGORY
APPLICATIONS

The picture don't represent the real number of conductors
Shielded Cable for Data (See Data Network Catalogue)
Data transmissions and electronics

- A:** Grey Soft **PVC** Sheath. Outer cable diam. Ø 8,20 (±0,20) mm.
B: Braided Shielding O.F.C. Tinned Copper covering 85% + Drain Wire
C: Cores Insulation with Soft **PVC**. Core diam. Ø 1,10 (±0,20) mm.
Color Code DIN 47100 Standards: White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet, Grey/Pink, Red/Blue, White/Green, Brown/Green, White/Yellow, Yellow/Brown, White/Grey, Grey/Brown, White/Pink, Pink/Brown. Stranded with waste filler between conductors and wrapped with Mylar Tape.
D: Stranded O.F.C. Red Copper, formation 18x0,10 mm.
Nom. Cross section 20x0,14 mm².

MARKING
CUSTOM
PRODUCTION

tasker® C251 LiYCY 20x0,14 - 26 AWG LOW VOLTAGE Computer Cable
Made In Italy
This product may be custom produced also in **LSZH, PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	80 pF/mt
Capacity Core/Shield	150 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			