

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet **tasker® C262 – 3x1,00 mm²** **Power Cable 300/500 V**

FirestoP®



A

B

C

CATEGORY Power Cable (See Electronics Catalogue)
APPLICATIONS Energy and electrical installation.

- A:** PVC Sheath Available Black or White.
 Outer cable diam. Ø 7,00 (±0,20) mm.
- B:** Core Insulation with PVC. Diam. Ø 2,50 (±0,20) mm.
 Color Code: Blue, Brown, Yellow/Green.
- C:** O.F.C. red copper formation with 0,20 mm elementary wires.
 Nom. Cross section 3x1,00 mm².

MARKING **tasker®** 3G1 mm² H05VV-F IEMMEQU <HAR>

Cable Properties

Conductor Resistance	18,80 Ω/Km
Max Rated Voltage U ₀ /U	300/500 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 16.05.16