

Technical Datasheet

tasker® TSK1126 - 1x4,00 mm²

Shielded Speaker Cable



CATEGORY Shielded Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional loudspeakers and premade cables

- A:** Black Soft **PVC** sheath.
Outer Cable Diameter Ø 7,00 (±0,10) mm.
- B:** Shielding in O.F.C. red copper spiral covering 100% with a formation of 128x0,20 mm. Nom. section of the shield 1x4,00 mm².
- C:** Core Insulation with grey PVC.
Dimension Ø 4,00 (±0,10) mm.
- D:** O.F.C. red copper formation 128x0,20 mm.
Nom. Cross section 1x4,00 mm².

MARKING **tasker®** TSK1126 – 1x4,00 mm² - O.F.C. COAXIAL SHIELDED SPEAKER CABLE+
- Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			