

Technical Datasheet

tasker® T28 – 2x10 AWG



Flexible Loudspeaker Cable



CATEGORY	Flexible Speaker Cable
APPLICATIONS	Professional Loudspeakers and premade cables

- A:** Black Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 12,40 (±0,20) mm.
- B:** Core Insulation with **PVC**, colored one Red and one Black.
Diam. Ø 5,00 (±0,20) mm.
- C:** O.F.C. red copper formation 84x0,30 mm.
Nom. Cross section 2x10 AWG

MARKING	tasker® T28 2x10 AWG O.F.C. Loudspeaker Cable - FirestopP® - Made In Italy
CUSTOM PRODUCTION	This product may be custom produced also in L.S.Z.H. polymer, PE , PUR , with or without Metallic Armor.

Cable Properties

Conductor Resistance	2,75 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B/ 04.07.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			