

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Technical Datasheet

tasker® C151 – 2x1,00 mm²

Flat Power Cable 300/500 V FirestoP®



CATEGORY Power Cable (See Electronics Catalogue)
APPLICATIONS Energy and electrical installation.

- A:** Flat **PVC** Sheath Available in Black or White colors.
Outer cable dimension Ø 4,20x6,70 (±0,20) mm.
- B:** Core Insulation with **PVC**. Diam. Ø 2,50 (±0,20) mm.
Color Code: Blue, Brown.
- C:** O.F.C. red copper formation with 0,20 mm elementary wires.
Nom. Cross section 2x1,00 mm².

MARKING **tasker®** 2G1,00 mm² H05VV2-F IEMMEQU <HAR>

Cable Properties

Conductor Resistance	18,80 Ω/Km
Max Rated Voltage U₀/U	300/500 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 12.02.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			