

Technical Datasheet



tasker® T21 AR – 2x16 AWG

Armored Loudspeaker Cable **FirestoP®**



A	B	C	D
---	---	---	---

CATEGORY

Speaker Cable (See Audio Catalogue)

APPLICATIONS

Outdoor and Underground speaker installation.

- A:** Anti rodents **Metallic Armor** specific for Outdoor and underground installation, even in presence of rodents.
Outer Diam. Ø 8,40 (±0,20) mm.
- B:** Black Soft **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 7,40 (±0,20) mm.
- C:** Core Insulation with PVC Sheath, colored one Red and one Black..
Diam. Ø 2,20 (±0,20) mm.
- D:** O.F.C. red copper formation 28x0,25 mm.
Nom. Cross section 2x16 AWG.

MARKING

tasker® T21AR 2x16 AWG O.F.C. Loudspeaker Cable - FirestoP® - Made In Italy

CUSTOM

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

PRODUCTION

Cable Properties

Conductor Resistance	12,50 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
	X	Outdoor	Esterno			Mobile	Mobile			
	X	Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			